

Care and Maintenance

For proper care, always follow directions on each product label.

Initial Care:

1. Sweep, vacuum or dust mop.
2. Mist the area to be cleaned with Hartco Easy Clean and wipe with the Hartco Sh-mop.
3. For Pattern-Plus and Pattern-Plus 5000 floors without the Permion finish, apply Hartco Pattern-Plus Shine.

Routine Care:

1. Sweep, vacuum or dust mop as needed.
2. Wipe up spills with Hartco Easy Clean. For large areas, mist Easy Clean and wipe with the Hartco Sh-mop.
3. For Pattern-Plus and Pattern Plus 5000 floors without the Permion finish, apply Pattern-Plus Shine as needed (2-4 times per year).



Hartco Easy Clean:

- Specially formulated to clean virtually all Hartco floors.
- Easily cleans dirt, food spots and other soiled areas.
- Available in a large 32-ounce size.
- Available with the Hartco Sh-mop in one convenient Floor Care Kit. For proper care, always follow directions on each product label.
- Mats at all entrances help keep dirt and moisture from being tracked in.
- Area rugs are recommended in front of kitchen sinks. Do not use rugs with solid rubber or vinyl backings.
- Never damp mop with water. It may permanently damage the floor.
- Do not walk on your Hartco floor with worn out stiletto or spike heels.
- Do not roll or slide heavy objects directly upon the floor.
- Pet claws may scratch hardwood floors.
- Maintain proper climate controls. A temperature of 70° F (21° C) and relative humidity of 35% to 50% are ideal.

Use Hartco floor protectors on the feet of furniture to avoid scratches.

Water Spots :

- Remove with a soft cloth dampened with Hartco Easy Clean or white vinegar.

Food Spills:

- Clean promptly with Hartco Easy Clean.

Rubber Heel Marks, Crayon, Gum or Asphalt Deposits:

- Dampen a clean cloth with Hartco Wipe Clean and rub to remove.

Scratches:

Use Hartco's Touch-up Kit on PearlWhite parquet, Plank and Strip floors. For light scratches or color loss on Hartco Acrylic Impregnated floors without Permion finish, apply Hartco Spray Tone. To repair

deep scratches on Hartco Acrylic Impregnated floors without Permion finish, lightly abrade with 00 steel wool or 400 grit sandpaper; then apply Hartco Spray Tone. Repairs may also be made by replacing individual slats or units.